



The XR200/XRS-3 Mains Power Adapter has been designed to replace the generator's standard rechargeable batteries in scenarios where it is necessary to use the XR200 or XRS-3 X-ray generators continuously.



Technical Specifications:

AC/DC-Mains adapter

Input:	85 VAC – 264 VAC, 47 Hz – 63 Hz, IEC 120VDC – 350VDC Active PFC
Fuse:	10 A, primary side
Output:	13.2VDC, 22 A, 290 W, Constant short circuit protected
Dimensions:	285 x 170 x 55 mm

Battery-housing with connecting cable

Cable length:	3 m
Connector:	LEMO 2B.304, 4-pin

Environmental conditions

Operating temperature:	-20 °C up to +71 °C
Humidity:	20 % – 90 %, not condensing

Total weight: 2.4 kg

The kit is designed to meet following Standards and Regulations:

- Electric safety acc. to 73/23/EEC:	TUEV EN60950-1, UL60950-1, c-UL CSA60950-1, EN50178
- Electromagnetic interference EMI:	FCC CFR 47 Part 15 Class B / EN55011-B / EN55022-B
- Electromagnetic susceptibility EMS:	EN 61000-3-2 / EN61000-4-,2,3,4,5,6,8,11
- ROHS:	According to 2002/95/EC
-CE-label:	According to CE Directive 93/68/EEC.

Specifications are subject to change without notice.